

Chargers designed to optimize the performance and life of your ODYSSEY® battery

ODYSSEY® battery chargers are designed to efficiently charge ODYSSEY batteries and other quality brands of 12-volt Absorbed Glass Mat (AGM), flooded lead acid batteries and 12-volt lithium batteries (LiFePO4, Li-Fe, Li-iron, LFP).

Whether you need a charger for a car, boat or professional workshop, we have a model that's right for you, offering performance, quality and speed in a rugged casing.

- World's first combined AGM² TPPL and lithium charger
- Fast, fully automatic charging after selecting battery type
- Lightweight and highly portable
- Built-in temperature controls
- Battery status indicator
- 5, 15 and 25 Amp models available
- Compatible with most[†] 12-volt battery types
- 3-year warranty



See battery charging mode and status at a glance.



Extremely portable and impact resistant.



DC charging clamps are fast and easy to connect.

PART NUMBER	Description	Nominal		Cable Length	Length	Width	Height	Weight	Box Size	ODYSSEY Battery AGM ² Amp Hour Range*
		Volts	Amps	(power/lead)	[mm]	[mm]	[mm]	[kg]	[LxWxH mm]	at 10 hour rate
OBC-5U or E [†]	5 Amp Charger	12	5	1.8 m each	168	66	38	0.6	279.4 x 152.4 x 57.15	5 Ah to 50 Ah
OBC-15U or E †	15 Amp Charger	12	15	1.8 m each	235	130	64	2.1	317.5 x 222.25 x 76.2	15 Ah to 150 Ah
OBC-25U or E [†]	25 Amp Charger	12	25	1.8 m each	235	130	64	2.1	317.5 x 222.25 x 76.2	25 Ah to 250 Ah

[†] Charges the following 12V batteries: Flooded/Wet, EFB, MF, AGM, GEL, LiFePO4, Li-Fe, Li-iron, LFP

IP65 rated (splash and dust proof) 8 step fully automatic charging cycle



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland EnerSys Asia No. 85, Tuas Avenue 1 Singapore 639518 Tel: +65 6558 7333

Want more info? Scan code to access the ODYSSEY® Battery Literature Library











^{*} Recommended charging rates for ODYSSEY AGM² battery: 10% Ah Min, 40% Ah Optimum, 100% Ah Maximum