

## **ODYSSEY® Motorcycle Batteries**

Rated Operating Temperature -40°C to 45°C All values shown are nominal unless otherwise noted.

NEW PART NUMBER (Old Part Number)	PHCA** 5 sec [Amps]	CCA* [Amps]	20 HR Rate [Ah]	Reserve Capacity [Minutes]	Maximum Length [mm]	Maximum Width [mm]	Maximum Total Height [mm]	Maximum Container Height [mm]	Weight [kg]	Terminal	Maximum Torque [Nm]	Industry Cross Reference
ODS-AGM8E	310	100	8	9	138	86	99	99	2.5	M4 Receptacle	1.0	YTX7A-BS YTX9-BS
ODS-AGM15L	460	150	13	18	178	84	124	130	5.0	M6 Receptacle	5.6	YTX15L-BS
ODS-AGM14	565	220	14	18	149	87	146)	146	4.5	M6 Receptacle	5.6	YTX14 YTX14-BS GYZ16H
ODS-AGM16L	520	170	16	24	182	77	162	168	7.0	M6 Receptacle	5.6	51814 51913 YT19BL-BS
ODS-AGM20L	675	275	18	24	175	86	155	155	5.9	M6 Receptacle	5.6	YTX20L, YTX20L-BS YTX20HL, YTX20HL-BS GYZ20L, GYZ20HL
ODS-AGM30L	720	400	30	50	167	125	174	9.2	9.0	M6 Receptacle	5.6	YB30L-B, YIX30L YIX30L-BS, GYZ32HL 53030

\*Cold Start Performance S.A.E J537 Apr 2016

\*\*Pulse Hot Cranking Amps





**EnerSys World Headquarters** 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland EnerSys Asia No. 85, Tuas Avenue 1 Singapore 639518 Tel: +65 6558 7333

Want more info? Scan code to access the ODYSSEY® Battery **Literature Library** 

